		,	ΓΑΙ]-							
	ONE S	STOP	зно	PIN	CHIN	Δ							
309S S	Stainless Steel	l Coil/S	heet										
1.Stan	dard:												
AISI	309S;ASTM	A240/A	240M-A	A240 30	9;JIS G	4304	-SUS 3	309 ;U	NS-S309	08			
2.Type	e:												
Auster	nitic Stainless	Steel											
3.Surf	ace:												
NO.1-	309S NO.1;B	A- 309 S	5 BA ;2B	-309S 2	B ,etc								
4.Proc	essing Way:												
Hot R	olled,Cold Ro	olled											
5.Trea	tment:												
Pickle	d,Quenched,7	Tempere	d,Annea	aled									
6.Cher	mical Compos	sition:%	1										
A240	JIS G 4304	С	Mn	Р	S	Si	Cr		Ni	Mo	Ν	Cu	Other
309S	SUS309S	0.08	2.00	0.045	0.03	0.7 5	22.0-2	24	12-15				
7.Mec	hanical Prope	erty:											
A240	JIS G 4304	Tensile Strength MPa			Yield Strength MPa			Elongation in 2in.or 50mm,%		Hardness Rockwell B		Cold Bend	
309S	SUS309S	621			310			45		95			

8. Application Area:

Resistance of corrosion for AISI/SUS 309S stainless is excellent, Type 309S' content of carbon is lower than Type 309, which can improve the weldability of 309S. This material is mainly used in furnace parts, heating elements, boiler baffles, chemical processing equipment, etc.

TJC Stainless is the most competitive manufacture and supplier of **309S** stainless steel in thickness 0.3mm-80mm and width up to 2200mm.Other special requests about specification, please contact us.

Attachment:

Mill Certificate Sample for 309S Stainless Plate/Sheet/Coil.

Keyword:Type	309S;AISI	309S,A240	309S,SUS	309S, STAINLESS
STEEL,PLATE,SHEP	ET,COIL			